Case No.: 56964US002

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original): An optical manifold comprising:

a unitary body having an input end and an output end;

said input end having a plurality of input openings in a first ordered arrangement;

said output end having a plurality of output openings in a second ordered arrangement which differs from that of said first ordered arrangement;

said unitary body further comprising a plurality of integrally formed passageways, wherein each of said passageways connects a single input opening with a single output opening.

- 2. (Original): The optical manifold of claim 1, wherein the unitary body is formed of a polymeric material.
- 3. (Original): The optical manifold of claim 2, wherein the unitary body contains voids to reduce the amount of polymeric material required.
- 4. (Original): The optical manifold of claim 1, wherein the unitary body is formed of a metal.
- 5. (Original): he optical manifold of claim 1, wherein the unitary body is formed by an additive manufacturing process.
- 6. (Original): The optical manifold of claim 1, wherein the passageways have been smoothed by abrasive laden slurry polishing.
- 7. (Original): The optical manifold of claim 1, wherein at least one ruggedized cable attachment is provided at the input end or the output end of the unitary body.

Application No.: 09/927663 Case No.: 56964US002

8. (Original): The optical manifold of claim 7, wherein the at least one ruggedized cable attachment anchors load bearing portions of a ruggedized cable to the unitary body to provide strain relief.

- 9. (Original): The optical manifold of claim 1, wherein at least one multifiber termination has been made at the input end or the output end of the unitary body.
- 10. (Original): The optical manifold of claim 1, wherein the unitary body has been enclosed within a protective housing.
- 11. (Original): The optical manifold of claim 10, wherein at least one optical connector is anchored to the protective housing.
- 12. (Original): The optical manifold of claim 1, wherein the unitary body has been mounted to a plug-in card to form an optical shuffle module.
- 13. (Original): The optical manifold of claim 12, wherein the optical shuffle module has been rack mounted.
- 14. (Previously Presented): An optical manifold comprising:

a body having plurality of plates, each of said plates having an input end and an output end;

each plate being formed with a plurality of channels spanning the entire length of each plate from the input end to the output end;

said body being constructed by arranging the plurality of plates in a stacked configuration to provide a plurality of input openings at the input end and a plurality of output openings at the output end, wherein each of said channels forms a passageway connecting a single input opening with a single output opening, and wherein the plurality of input openings are in a first ordered arrangement and the plurality of output openings are in a second ordered arrangement that differs from the first ordered arrangement.

Application No.: 09/927663 Case No.: 56964US002

15. (Original): The optical manifold of claim 14, wherein the at least one passageway is non-linear.

- 16. (Original): The optical manifold of claim 14, wherein at least two channels intersect on at least one plate.
- 17. (Original): The optical manifold of claim 14, wherein the plates are substantially rigid.
- 18. (Original): The optical manifold of claim 14, wherein the plates further comprise an alignment means for indexing the plates one to another.
- 19. (Original): The optical manifold of claim 14, wherein the channels are formed by milling each of said plates.
- 20. (Original): The optical manifold of claim 14, wherein the channels are formed by injection molding each of said plates.
- 21. (Original): An optical manifold comprising:
- a body having a plurality of hollow tubes, each of said tubes having an input end and an output end;
 - a first endplate having a plurality of input openings in a first ordered arrangement;
- a second endplate having a plurality of output openings in a second ordered arrangement which differs from said first ordered arrangement;
- said body being disposed between said first endplate and said second endplate, wherein each of said hollow tubes connects a single input opening with a single output opening.
- 22. (Original): The optical manifold of claim 21, wherein the tubes are flexible.
- 23. (Original): The optical manifold of claim 21, wherein the tubes are substantially rigid.

Case No.: 56964US002

24. (Original): The optical manifold of claim 23, wherein the tubes are formed of two semi-cylindrical halves.

25. (Original): The optical manifold of claim 21, wherein the tubes are color-coded.